

Enfis

LED Driver – 200W



The Power of Ingenuity

ENFIS 

Enfis 200W Driver

- Can drive either QUATTRO Mini or UNO Plus
- Active feedback enabling 100% lumen maintenance and precise colour/CCT management
- High performance and reliability at high ambient temperatures
 - High spec components and smart control
- High output in high ambient temperatures without risk of cut-out
 - Smart 2-stage dynamic thermal protection
- Enables RGBW/RGBA/Hi-CRI
 - 4-channel system
- Remote monitoring and control
 - DMX RDM



The Power of Ingenuity

ENFIS 

Key Features

- ⓔ **Key features for High Ambient Temperatures**
- ⓔ 2-stage dynamic thermal protection:
 - Thermal cut-out
 - Ensures protection of LEDs to maintain system life
 - Thermal dimming:
 - Ensures max output can be set as high as possible without peaks in ambient causing cut-out
 - Smooth control results in dimming being virtually unnoticeable
- ⓔ All components verified as OK operating in 60°C ambient
- ⓔ Power rating: 50W/channel



The Power of Ingenuity

Key Features

- **Key Features for High Ambient Temperatures**
- Component reliability: analysis of component failure at elevated ambient temperature.
 - Sensitive component: electrolytic capacitors:
 - Tend to fail with elevated temperature
 - Enfis have specified high-rated component
 - Rated to 105°C
 - 48,000 hour life at constant 70°C operating temp (measured component temperature in ambient of 60°C)



The Power of Ingenuity

ENFIS 

Key Features

E Other Key Features

E DMX capability:

- DMX in/out
- DMX RDM enabling remote:
 - On/off function
 - DMX channel programming
 - LED temperature monitoring
 - Dynamic thermal protection monitoring
 - Logging of luminaire running time

E Max current calibration:

- Standard: 1000mA
- Available range: 100mA to 2000mA/channel

E Dimming

- Analogue or PWM



The Power of Ingenuity

System Description

Ⓔ Power Input: 48V d.c. max: 5A

Ⓔ Output:

- Number of channels: 4
- Voltage range per channel: 16V – 42V
- Current range per channel: 100mA-2A
- Maximum power per channel: 50W

Ⓔ Control and Feedback

- Permanent temperature monitoring channel – can be customised to multiple channels through auxiliary inputs.
- 4 – channel efficient LED drivers based on switch mode technology
- Current and voltage monitoring of each channel
- Low voltage supply monitor

Ⓔ Driver Features

- Individual ON/OFF channel
- 8-bit Pulse Width Modulation (PWM) for dimming
- Pseudo random colour sequencing

Ⓔ Connectivity

- 4 auxiliary inputs available for switches, potentiometers etc.
- TTL RS-232 interface
- DMX – RS485 interface
- USB/Serial PC interface
- I2C interface available for customer requirements

Ⓔ Dimensions

- 170mm x 180mm x 70mm



The Power of Ingenuity

ENFIS